

	6.1 Automatic Cable Tying System	538
	6.2 Application Tooling for Cable Ties	544
	6.3 Application Tooling for	
	Cutting Plastic Ties.....	561
	Snappers.....	562
	Heat Shrinkable Tubing.....	563
	Non Shrinkable Tubing	565
	Braided Sleeves	568
	Identification	569





6.1 Automatic Cable Tying System

Automatic bundling up to Ø 20 mm	
Autotool 2000 CPK	538
Accessories for Autotool 2000 CPK	539
Cable ties for Autotool 2000 CPK	540
Waste-free bundling up to Ø 80 mm	
Autotool System 3080	541
Accessories for Autotool System 3080	542
Cable ties for Autotool System 3080	543



6.2 Application Tooling for Cable Ties

Product Selection	
Tool Overview for Cable Ties	544, 546
Flowchart for optimum tool selection	545, 546
Technical Information	
How to use a cable tie tool	547
Manual tensioning tool for cable ties with low profile head	
MK10-SB	549
Manual tensioning tool, simple version	
MK20, MK21	549
Manual tensioning tool plastic housing	
EVO7, EVO7SP	552
EVO9, EVO9HT, EVO9SP	553
Accessory for EVO family	
CALTOOL	552

Pneumatic tensioning tool metal housing

MK3PNSP2	550
----------	-----

Pneumatic tensioning tool plastic housing

MK7P	554
MK9P	555
MK9PSST	557

Manual tensioning tool for KR-Series

KR6/8	556
-------	-----

Pneumatic tensioning tool for KR8-Series

KR8PNSE	556
---------	-----

Manual tensioning tool for metal ties MBT-Series

MK9SST	557
KST-STG200	558

Manual tensioning tool for metal ties MBT-, MLT- and AMT-Series

HDT16	558
-------	-----

Manual tensioning tool for metal ties MST-Series

MST6	559
MST9	559



P	6.3 Product Selection	
	Tool Overview	560

	6.3 Application Tooling for Cutting Plastic Ties	
	Manual cutting tool for plastic ties	
	EVO cut	561

	6.3 Application Tooling for Snappers	
	Manual Tool	
	ASNP, MSNP snapper tools	562

	6.3 Application Tooling for Heat Shrinkable Tubing	
	Gas powered hot air tool	
	CHG900	563
	Electrical hot air tool	
	H6100	564

	6.3 Application Tooling for Non Shrinkable Tubing	
	Three-pronged pliers for sleeves and grommets	
	NA	565
	VA2.5/5 - reinforced	566
	K, S, SS	567

	6.3 Application Tooling for Braided Sleeves	
	Helagaine Braided Sleeving	
	HSG0 hot cutting tool	568

	6.3 Application Tooling for Identification	
	Manual Tool for Helafix HCR	
	Helafix HCT application tool	569



Automatic bundling up to Ø 20 mm

Autotool 2000 CPK

The Autotool 2000 CPK is an electrically operated and automated cable tying system. It has been developed to speed up bundling processes and to make the production more efficient. Besides the high speed bundling, this cable tying system is characterized by its simple operation and user-friendly ergonomics. The Autotool 2000 CPK offers a display for the settings and user information in 20 languages. One main feature of the Autotool 2000 CPK is the software "HT Data Management CPK".

This feature enables the easy parameterization of the tool for customers applications. The parameterization can easily be carried out via computer. Additionally the "HT Data Management CPK" offers an export function for the saved manufacturing data as well as further service functions. Therefore it ensures a consistent documentation for every binding process through the tool. The firmware of the AT2000 CPK tool enables various bundling and cutting functions. It is possible to define a loop diameter and to choose the length of an extended strap as an example. The function to cut with the tension released is of great value especially for applications with a very flexible bundling good (like silicone cables).

The Autotool 2000 CPK is ideally suited for handling high volume applications in wire harness facilities, automotive and industrial companies and in the packaging sector. With either the Bench mount kit CPK or the Overhead suspension CPK, the Autotool 2000 CPK is suitable for both stationary and flexible applications.

By using the optional Power pack CPK with control box the Autotool 2000 CPK can be integrated into fully automated production lines through a serial interface. Due to the removable handle less assembly space is needed.

Bandoleers of 50 cable ties as well as reels of 3,500 cable ties can be used.

Features and benefits

- Electrically operated cable tying system
- Power supply through Power pack CPK - Input: 100-240 V a.c., 50/60 Hz; Output: 25.2 V d.c., max. 150 W
- Integration into fully automated production lines (Power pack CPK with control box necessary)
- Cycle time 0.8-1.2 sec. depending on quality and force
- Stationary and flexible use with devices possible
- HT Data Management CPK software (included) - for extensive data evaluation and monitoring of the tensioning process
- User-friendly menu in various languages included
- Process-reliable, constant and reproducible bundling and cutting up to Ø 20 mm
- Removable handle for space-saving integration



www.HellermannTyton.com/AT2000CPK-cat22



Autotool 2000 CPK.



HT Data Management CPK - software for Autotool 2000 CPK.



Power pack CPK for Autotool 2000 CPK.

TYPE	Description	Article-No.
Autotool 2000 CPK	Autotool 2000 CPK	106-00000
Power pack CPK	Power pack CPK	106-00100
Power pack CPK with control box	Power pack CPK with control box	106-00110

Subject to technical changes.

Power Supply	Electronically operated
Cycle Time	0.8-1.2 sec. depending on quality and force
Weight	1.8 kg
Tension Setting	Adjustable





Automatic bundling up to Ø 20 mm

Accessories for Autotool 2000 CPK

Features and benefits

- Bench mount kit CPK for stationary use
- Overhead suspension CPK for flexible use
- Wire retainer HH20 raises the bundle off the harness board at optimum height and allows the operator to eliminate handling the bundle when applying ties
- Force measurement device CPK to measure the linear tensile force of the Autotool 2000 CPK. Available with grip mount or robot adapter




Bench mount kit CPK with foot pedal (also shown: Autotool 2000 CPK, Power pack CPK and T18RA3500).

TYPE	Description	Article-No.
Bench mount kit CPK	Bench mount kit CPK	106-00040
Force measurement device with grip mount CPK	Force measurement device with grip mount CPK	106-29010
Force measurement device with robot adapter CPK	Force measurement device with robot adapter CPK	106-29011
HH20	HH20 wire retainer	120-00080
Overhead suspension CPK	Overhead suspension CPK	106-00050

Subject to technical changes.



Overhead suspension CPK (also shown: Autotool 2000 CPK, Power pack CPK and T18RA3500).



Harness board accessory HH20.



Application with the Bench mount kit CPK.



Add items to your watchlist!
www.HT.click/9-539



Automatic bundling up to Ø 20 mm

Cable ties for Autotool 2000 systems

The inside-serrated cable ties are designed for use specifically in the automatic cable tying systems. The Autotool 2000 CPK is ideally suited for handling high volumes applications in wire harness facilities, automotive and industrial companies as well as the packaging sector.


Features and benefits

- Available in bandoleers of 50 cable ties or reels of 3,500 cable ties
- Repetitive tension on the bundles
- Easily recyclable



Cable ties for Autotool 2000 systems.

MATERIAL	Polyamide 6.6, heat stabilised (PA66HS)	Polyamide 6.6, heat and UV-resistant (PA66HSW)	Polyamide 4.6 (PA46)
Operating Temperature	-40 °C to +105 °C, (+145 °C, 500 h)		-40 °C to +150 °C, (+195 °C, 500 h)
Flammability	UL 94 V2		



Bandoleer T18RA



Please find the corresponding Bundling Clips on page 136.

TYPE	Bundle Ø max.	N	Colour	Material	Pack Cont.	Article-No.
T18RA50	20.0	80	Black (BK)	PA66HSW	2,000 pcs.	120-40020
T18RA3500	20.0	80	Black (BK)	PA66HSW	3,500 pcs.	120-50010
	20.0	80	Natural (NA)	PA46	3,500 pcs.	120-46009
T18RA50	20.0	80	Natural (NA)	PA66HS	2,000 pcs.	120-40019
T18RA3500	20.0	80	Natural (NA)	PA66HS	3,500 pcs.	120-50009

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.
More colours on request. Please contact us.



= Minimum Loop Tensile Strength for Cable Ties (newton)

Halogen-free according to the interdictions of the GADSL list and compulsory registration of the SVHC list.




For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

www.HT.click/9-540





Waste-free bundling up to Ø 80 mm

Autotool System 3080

The Autotool System 3080 is an automated and electric cable tying system. It has been developed to speed up bundling processes and operates waste-free.

The advantage of three quick-changeable jaw sizes allows the Autotool System 3080 to adapt perfectly to different bundle diameters up to Ø 80 mm.

With either the Bench mount kit 3080 or the Overhead suspension 3080, the Autotool System 3080 is suitable for both stationary and flexible applications. The Autotool System 3080 can also be integrated into fully automated production lines.

Custom designed jaws are available to enable bundling of foot parts on production lines.

Features and benefits

- Electrically operated cable tying system (Power pack 3080 necessary)
- Power pack 3080 - Input: 240/150 V a.c., 50/60 Hz; Output: 48 V d.c., max. 150 W
- High quality, waste-free bundling up to Ø 80 mm with flush cut off
- Jaws with diameters of 30, 50 and 80 mm - included in delivery
- Cycle time 1.1-2.4 seconds depending on bundle diameter
- Integration into Bench mount kit 3080 or Overhead suspension 3080 possible
- Integration into fully automated production lines possible
- Foot part bundling with custom jaw design Ø 50 mm



www.HellermannTyton.com/ATS3080-cat22



Autotool System 3080.



Autotool System 3080 with three different jaws - to optimize the cycle time for different bundle diameters.

TYPE	Description	Article-No.
ATS3080	Autotool System 3080	102-00000
Power pack 3080	Power pack 3080	102-00100

Subject to technical changes.



Power pack 3080.

Power Supply	Electrically operated
Cycle Time	1.1-2.4 sec. depending on bundle diameter
Weight	2.068 kg
Tension Setting	Adjustable



Add items to your watchlist!
www.HT.click/9-541





Waste-free bundling up to Ø 80 mm

Accessories for Autotool System 3080

Features and benefits

- Bench mount kit automatic 3080 in fully automated production lines
- Bench mount kit horizontal 3080 for horizontal use in fully automated production lines
- Bench mount kit 3080 for stationary use, foot pedal included
- Overhead suspension 3080 for flexible use




Bench mount kit 3080 with foot pedal (also shown: Autotool System 3080, Power pack 3080 and consumables).



Optional: Bench mount kit 3080 with table board.



Packaging application with Bench mount kit horizontal 3080.



Overhead suspension 3080 (also shown: Autotool System 3080 and consumables).

TYPE	Description	Article-No.
Bench mount kit automatic 3080	Bench mount kit automatic 3080	102-00042
Bench mount kit horizontal 3080	Bench mount kit horizontal 3080	102-00041
Bench mount kit 3080	Bench mount kit movable 3080	102-00040
Overhead suspension 3080	Overhead suspension 3080	102-00050

Subject to technical changes.





Waste-free bundling up to Ø 80 mm

Cable ties for Autotool System 3080

The outside serrated strap is perfectly suitable for sensitive surfaces and can be used for bundling and fixing of cables, pipes and hoses, as well as for bag sealing.

The materials are particularly appropriate for high volume bundling applications in cable assembly, automotive, industrial and packaging applications.

Features and benefits

- Innovative two-piece consumables: closure and strap
- Outside serrated strap protects the bundle
- Available on reels of 500 m strap and 5,000 pcs. closures



Closures and strap for Autotool System 3080.


MATERIAL	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)	Polyamide 6.6, heat and UV-stabilised (PA66HSUV)
Operating Temperature	-40 °C to +95 °C, (+105 °C, 5000 h; +145 °C, 500 h)	-40 °C to +105 °C, (+145 °C, 500 h)
Flammability	UL 94 HB	UL 94 V2

RoHS ✓

RoHS ✓



Please find the corresponding Bundling Clips on page 136.



TYPE	Description	Bundle Ø max.	N	Colour	Material	Pack Cont.	Article-No.
Closures Black ATS3080	Closures Black ATS3080	80.0	225	Black (BK)	PA66HSUV	5,000 pcs.	102-66210
Closures Natural ATS3080	Closures Natural ATS3080	80.0	225	Natural (NA)	PA66HSUV	5,000 pcs.	102-66209
Strap Black ATS3080	Strap Black ATS3080	80.0	225	Black (BK)	PA66HIRHSUV	500 m	102-66110
Strap Natural ATS3080	Strap Natural ATS3080	80.0	225	Natural (NA)	PA66HIRHSUV	500 m	102-66109

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

= Minimum Loop Tensile Strength for Cable Ties (newton)



Add items to your watchlist!
www.HT.click/9-543



Tensioning Tools for Cable Ties



MK10-SB.
See page 549

1



MK20, MK21.
See page 549

2, 3



MK3PNSP2.
See page 550

5



EVO7/EVO7SP.
See page 552

6



MK7P.
See page 554

8



EVO9/EVO9SP.
See page 553

10



EVO9HT.
See page 553

11



MK9P.
See page 555

12

Tensioning Tools for Cable Ties KR-Series



KR6/8.
See page 556




13



KR8PNSE.
See page 556

14

Flowchart for optimum tool selection



Tensioning Tools for Metal Ties



MK9SST.
See page 557

15



MK9PSST.
See page 557

16



HDT16.
See page 558

17



KST-STG200.
See page 558

18



MST6.
See page 559


19



MST9.
See page 559

20


Flowchart for optimum tool selection




How to use a cable tie tool (using an EVO7 as an example)




1. Use tension adjustment knob to select your desired tension setting.



2. Cinch a nylon HellermannTyton cable tie around the bundle.



3. Insert strap of cable ties through side opening of nosepiece.



4. Place front of nosepiece flush to the head of the cable tie.



5. Pull trigger until cable tie tensions and cuts.

Tool testing - Determination of tensions

To date, no generally applicable test method has been established on the market. The companies within the HellermannTyton group work with an usual force meter with minimum 10 kHz frequency of data sampling to determine the tensile forces of the tools and to guarantee the quality of the tools.

It is more difficult to test cable tie tools than would appear at first glance. It is of supreme importance to comply with a standardised test procedure and consistent test conditions. This means for instance the size and thus the cross-section of the cable ties, but also the water content of the tie. A test using different ties and / or different conditioning can easily lead to different values.

In general, the speed of cut-off, the position of the tool with respect to the cable tie, the condition of the wearing parts in the tool and the state of the cable tie play a fundamental role in the determination of tensile forces.

Therefore we must point out that any values we provide must only ever be regarded as guide values for your information. The values cannot be transferred into practice "one for one".

In our user instructions, we specify an adjustment range for each type of cable tie. If tension values must be documented or comply with a specification, we recommend that you adjust them with the aid of the

force meter. Also, as a guideline, half the minimum holding strength of the cable tie should be used as tensile force.

The minimum tensile strength (also referred to as minimum unlocking strength) is the least force which the cable tie can withstand before it tears or stretches. This strength is determined using a threaded tie, hence the following formula should be used for guidance as to the correct tensile force of the tool:

$$\frac{\text{Min. tensile strength}}{2} = \text{recommended tensile force}$$

Example:

$$T50R = \frac{225 \text{ N minimum tensile strength}}{2}$$

$$\frac{225 \text{ N}}{2} = 112.5 \text{ N recommended tensile force according to formula}$$

The tensile force can of course be adjusted up or down, in line with the corresponding application.

Please bear in mind that this statement applies only to HellermannTyton products. Cable ties from other manufacturers may require a higher or lower force setting.

In order to secure the device after it has been adjusted using the force meter against manipulation or unintentional maladjustment, HellermannTyton offers an adjustment safety cap (Art. No.: 110-07200 for MK7HT, MK7P, MK9SST, MK9P) which you can push onto the device

after removing the adjustment unit (loosening a screw is all it takes to remove).

After a period of time, to be defined, you test the device again and if necessary re-adjust it. The problem of determination of forces depends on the individual case and has no direct connection with the quality of our product. An exact value for each setting (e. g. in newtons), without stating a tolerance, cannot be confirmed.

Test set-up with a usual force meter and EVO7 cable tie tool.



The following describes how to check the tension force of a manual tensioning tool.

1. Lay the cable tie (green) into the fixture (A).
2. Bring the nose piece of the tensioning tool (B) flush to the test block (C).
3. Insert the strap of the cable tie into the tensioning tool and pull the strap flush against the fixture (A).
4. Re-set the force meter (D) to zero.
5. Pull the trigger of the tensioning tool continuously until the cable tie is cut.
6. The tension force achieved at the cut off point is determined.



Manual tensioning tool for cable ties with low profile head

MK10-SB up to 9.5 mm strap width

Features and benefits

- Ideal for easy handling of entire HellermannTyton RPE, PE and LPH series
- Tensions and cuts off pre-looped cable ties flush at the head



MK10-SB.

TYPE	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MK10-SB	9.5	2.5	0.372 kg	110-10001

All dimensions in mm. Subject to technical changes.

Manual tensioning tool for cable ties, simple version

MK20 up to 4.8 mm strap width

MK21 up to 7.6 mm strap width

Features and benefits

- Lightweight, ergonomic tools
- For tensioning and cutting standard cable ties 4.8 - 7.6 mm width
- Ideal for on-site assembly
- Mounted and pretensioned ties are cut off by twisting tool
- Simply apply cable tie, tension and twist to cut



Manual tensioning tools MK20 and MK21.

TYPE	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MK20	4.8	1.5	0.05 kg	110-20006
MK21	7.6	2.5	0.05 kg	110-21016

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!

www.HT.click/9-549





Pneumatic tensioning tool metal housing

MK3PNSP2 up to 4.8 mm strap width

Features and benefits

- Pneumatic tensioning tool
- Tough metal housing
- For cable ties up to 4.8 mm width
- For consistent tensioning and automatically flush cutting
- Infinitely adjustable tension force
- High application speed
- Reliable and low maintenance



The pneumatic tensioning tool MK3PNSP2 for plastic cable ties with max. width of 4.8 mm.

Air Supply	non oiled, oiled
Air Pressure (min.)	5.5 Bar
Air Pressure (max.)	6 Bar
Hose Internal Diameter	4.0 mm
L x H x W	approx. 225 x 140 x 40 mm



TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MK3PNSP2	MK3PNSP2	4.8	1.5	0.555 kg	110-03400
SP MK3PNSP2 air hose 3 meters	Air hose, complete	-	-	0.139 kg	110-30002
SP MK3PNSP2 cutting blade	Replacement Blade	-	-	0.001 kg	110-30101

All dimensions in mm. Subject to technical changes.





The EVO family delivers maximum performance whilst protecting muscles and joints

The next generation of application tools impresses with its advanced technology.

With the EVO family HellermannTyton has developed truly ergonomic cable tie application tools that are unique in the market, perfectly combining convenience with function. **The heart of the EVO family is the innovative TLC-technology (Tension/Lock/Cut).** This is designed to revolutionise the application of cable ties by significantly reducing the cutting effort. The EVO family cuts cable ties with ease, delivering a flush clean finish with no excess strap, whilst enormously reducing physical strain on the user.



The patent-pending TLC-technology delivers increased productivity:

- Application force and effort are significantly reduced
- Precise cutting of the cable tie right at the head
- Smooth fastening of the cable tie without recoil
- Protects muscles and joints and herewith the health of the user

Perfect cutting made easy with the EVO family:

From precise preliminary settings to the perfect cut, the EVO family allows an even lighter, gentler and easier cable tie application than ever before. The TLC-technology makes all the difference!



1. Tension

Tension the cable tie as usual. Use the tension adjustment knob to select the desired tension setting.



2. Lock

The locking mechanism detects when the desired tension is reached, locking the tie in place prior to cutting. No manual pressure is required to hold the cable tie in place.



3. Cut

For the final cut, very little effort is needed. By simply pulling the trigger back a little to cut the tie. Without recoil and vibration.



Manual tensioning tool plastic housing

EVO7 up to 4.8 mm strap width

HellermannTyton's EVO7 mechanical hand tool was ergonomically designed to reduce the risks of repetitive stress injuries to operators while concurrently increasing productivity. The EVO7 Tension/Lock/Cut Technology delivers performance, safety and comfort for the operators. Available in a standard grip span (EVO7) or short grip span (EVO7SP), for smaller hands. Additional accessories are available.

Features and benefits

- Ergonomic, slip-proof handle for a comfortable and secure grip
- Extremely low-maintenance
- Fast and precise application with minimum effort (TLC mechanism)
- Convenient and simple tension adjustment
- Extended, slim nose for use in narrow spaces
- Housing made of resilient and lightweight glass fibre-reinforced polyester
- Standard grip span (90 mm) and short grip span (80 mm) available



The EVO7: Maximum performance with minimum effort.



www.HellermannTyton.com/EVO7-cat22

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
EVO7	EVO7	4.8	1.5	0.275 kg	110-70129
EVO7SP	EVO7SP	4.8	1.5	0.272 kg	110-70130
SP EVO7 Blade Kit	Blade-Kit	-	-	0.002 kg	110-70106

All dimensions in mm. Subject to technical changes.

CALTOOL for calibration of EVO family

The CALTOOL serves for the fine or readjustment of the EVO family.

Features and benefits

- The factory setting (setting 0-8) of the EVO family can be changed



CALTOOL for calibration of EVO family.

TYPE	Description	Weight	Article-No.
EVO Calibration Tool	Calibration tool	0.032 kg	110-70089

All dimensions in mm. Subject to technical changes.





Manual tensioning tool plastic housing

EVO9 up to 13.5 mm strap width

The EVO9 is available in a standard grip span 90 mm (EVO9) or short grip span 80 mm (EVO9SP), for smaller hands. Both tools perform between 53 N and 307 N. The EVO9HT (high tension) was designed to apply HellermannTyton cable ties from 120 N until 516 N with a maximum width of 13.5 mm.

Features and benefits

- Standard grip span (90 mm) and short grip span (80 mm) available
- Ergonomic, slip-proof handle for a comfortable and secure grip
- Extremely low-maintenance
- Fast and precise application with minimum effort (TLC-technology)
- Convenient and simple tension adjustment
- Integrated 3 position quick adjustment override (EVO9/EVO9SP/EVO9HT)
- Housing made of resilient and lightweight glass fibre-reinforced polyester



The EVO9 with TLC technology.

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
EVO9	EVO9	13.5	2.0	0.357 kg	110-80002
EVO9SP	EVO9SP	13.5	2.0	0.361 kg	110-80003
EVO9HT	EVO9HT	13.5	2.0	0.364 kg	110-80017
SP EVO9 Blade	EVO9 Blade	-	-	0.002 kg	110-80037

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!

www.HT.click/9-553





Pneumatic tensioning tool plastic housing

MK7P up to 4.8 mm strap width

The MK7P pneumatic bundling tool sets a new benchmark for the rational application of ties in the industrial production process. Improved compressed air supply moves the tensioning piston faster than in comparable tools.

Features and benefits

- Pneumatic tensioning tool
- Light glass-fibre-reinforced housing
- For cable ties up to 4.8 mm width
- For consistent tensioning and automatically flush cutting
- Infinitely adjustable tension force
- High application speed



The pneumatic tensioning tool MK7P for plastic cable ties with max. width of 4.8 mm.



The easy to use quick-set-knob.

Air Supply	non oiled, oiled
Air Pressure (min.)	3 Bar
Air Pressure (max.)	6 Bar
Hose Internal Diameter	4.0 mm
L x H x W	approx. 220 x 170 x 40 mm

RoHS

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MK7P	MK7P	4.8	1.5	0.87 kg	110-07100
SP MK3PNSP2 air hose 3 meters	Air hose, complete	-	-	0.139 kg	110-30002
SP MK7P replacement blade	Replacement Blade	-	-	0.001 kg	110-07111
SP MK7/MK9 Lock cap tensioning knob	Lock cap tensioning knob	-	-	0.011 kg	110-07200

All dimensions in mm. Subject to technical changes.





Pneumatic tensioning tool plastic housing

MK9P up to 13.5 mm strap width

The MK9P is constructed with heavy duty parts to ensure optimum performance. It is ideally designed to apply heavy-duty ties like they are used in vehicle construction like trucks, busses and railways.

Features and benefits

- Pneumatic tensioning tool
- Glass-fibre-reinforced housing
- For cable ties up to 13.5 mm width
- For consistent tensioning and automatically flush cutting
- Infinitely adjustable tension force
- High application speed
- Holding ring for a balancer
- Optional with lower or upper air attachment



The pneumatic tensioning tool MK9P for plastic cable ties with max. width of 13.5 mm.



MK9P is also available with upper air attachment.

Air Supply	non oiled, oiled
Air Pressure (min.)	3 Bar
Air Pressure (max.)	6 Bar
Hose Internal Diameter	4.0 mm
L x H x W	approx. 280 x 200 x 55 mm



TYPE	Description	Strap Width max.	Strap Thickness max.	Air att. Position	Weight	Article-No.
MK9P	MK9P	13.5	2.5	lower air connection	0.82 kg	110-09100
MK9P w/ Upper air	MK9P	13.5	2.5	top air connection	1.057 kg	110-09110
SP MK3PNSP2 air hose 3 meters	Air hose, complete	-	-	-	0.139 kg	110-30002
SP MK7/MK9 Lock cap tensioning knob	Lock cap tensioning knob	-	-	-	0.011 kg	110-07200
SP MK9P replacement blade	Replacement Blade	-	-	-	0.004 kg	110-09111

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!
www.HT.click/9-555





Manual tensioning tool for KR-Series

KR6/8

Application tool KR6/8 crimps the glass-fibre-reinforced locking pin of the KR seal and leads to plastic deformation of the tie ends. This produces a very proof permanent connection.

Features and benefits

- Tough metal tool for applying KR cable ties only
- For tensioning, fixing and cutting KR cable ties
- Simply change the front plate to apply 6 mm or 8 mm straps



The manual tensioning tool KR6/8 for KR-Series cable ties.

TYPE	Description	For Ties	Strap Width max.	Weight	Article-No.
KR6/8	KR6/8	KR6, KR8	8.0	0.69 kg	121-00680
SP KR6/8 replacement blade	Replacement blade	KR6, KR8	-	0.002 kg	122-68019

All dimensions in mm. Subject to technical changes.

Pneumatic tensioning tool for KR8-Series

KR8PNSE

Application tool KR8PNSE crimps the glass-fibre-reinforced locking pin of the KR seal and leads to plastic deformation of the tie ends. This produces a very proof permanent connection.

Features and benefits

- Pneumatic tool with tough metal housing
- For applying KR8 cable ties only
- For tensioning, fixing and automatic cutting KR8 cable ties
- Tension force can be adapted depending on air pressure
- Holding ring for a balancer



The pneumatic tensioning tool KR8PNSE for KR8-Series cable ties.

Air Supply	non oiled, oiled
Air Pressure (min.)	3 Bar
Air Pressure (max.)	4 Bar
Hose Internal Diameter	6.0 mm
L x H x W	approx. 320 x 210 x 50 mm

RoHS

TYPE	Description	For Ties	Strap Width max.	Weight	Article-No.
KR8PNSE	KR8PNSE	KR8	8.0	1.537 kg	121-00889
SP KR8PNSE replacement blade	Replacement Blade	KR8	-	0.002 kg	122-80032

All dimensions in mm. Subject to technical changes.





Manual tensioning tool for metal ties MBT-Series

MK9SST up to 16.0 mm strap width

The MK9SST is constructed with heavy duty parts to ensure optimum performance. It is designed to apply our MBT cable ties with a strap width of up to 16 mm. The tool is ideally suited for use in most arduous environments such as found on board ships, oil rigs, constructions or in nuclear power stations.

Features and benefits

- Glass-fibre-reinforced housing
- Ergonomic design
- Consistent tensioning and automatic cutting of metal ties MBT-Series
- Infinitely adjustable tension force combined with two-step quick adjustment



MK9SST.

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MK9SST	MK9SST	16.0	0.5	0.508 kg	110-95000
SP MK9SST replacement blade	Replacement Blade	-	-	0.004 kg	110-95273

All dimensions in mm. Subject to technical changes.

Pneumatic tensioning tool for metal ties MBT-Series

MK9PSST up to 16.0 mm strap width

The MK9PSST pneumatic stainless steel tool is constructed with heavy-duty parts to ensure optimum performance in demanding environments. It is ideally designed to apply stainless steel metal ball tie series (MBT) up to 16.0 mm width.

Features and benefits

- Unique levels of repeatability and accuracy
- High application speed and low maintenance
- Improved compressed air supply for faster tensioning piston movement
- Shorter processing time and greater volume of connecting tie application
- Ergonomic design
- Automatic ejection of cut-off cable tie end
- Ideally designed to apply stainless steel MBT-Series up to 16.0 mm width
- On air pressure between 3 and 6 bar



MK9PSST.

Air Supply	non oiled, oiled
Air Pressure (min.)	3 Bar
Air Pressure (max.)	6 Bar
Hose Internal Diameter	4.0 mm
L x H x W	approx. 280 x 200 x 55 mm

RoHS

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MK9PSST	MK9PSST	16.0	0.5	0.972 kg	110-95350
SP MK9PSST replacement blade	Replacement Blade	-	-	0.004 kg	110-95307
SP MK7/MK9 Lock cap tensioning knob	Lock cap tensioning knob	-	-	0.011 kg	110-07200

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!
www.HT.click/9-557





Manual tensioning tool for metal ties MBT-, MLT- and AMT-Series

HDT16 up to 16.0 mm strap width

The HDT16 application tool is designed for installing heavy duty stainless steel cable ties within a range of industries such as shipbuilding, oil rigs, mining and mass transit. The tool can easily be adjusted making it suitable for applying both MBT, MLT and AMT cable ties with a strap width of up to 16 mm.

Features and benefits

- Two way nose piece for use with MBT-Series and AMT-, MLT-Series stainless steel cable ties
- Easy adjustment of the handles to ensure the most ergonomic position for the operator
- Integrated cutting mechanism delivering a flush cut and professional finish every time
- The ideal tool for achieving a perfect installation of MBT, MLT and AMT cable ties



HDT16.



www.HellermannTyton.com/HDT16-cat22

TYPE	Strap Width max.	Strap Thickness max.	Weight	Article-No.
HDT16	16.0	0.8	0.78 kg	110-40000

All dimensions in mm. Subject to technical changes.

Manual tensioning tool for metal ties MBT-Series

KST-STG200 up to 12.3 mm strap width

The KST-STG200 application tool is designed for installing heavy duty stainless steel cable ties within a range of industries such as shipbuilding, oil rigs, mining and mass transit. The tensioning strength can be adjusted while pulling the trigger. The tool is easy to handle and far more reliable than trying to tension the ties by hand.

Features and benefits

- Tough metal tool
- Operator controlled tensioning
- Cut off by pulling the hand lever



KST-STG200.

TYPE	Strap Width max.	Strap Thickness max.	Weight	Article-No.
KST-STG200	12.3	0.3	0.562 kg	110-09950

All dimensions in mm. Subject to technical changes.





Manual tensioning tool for metal ties MST-Series

MST6 for 5.9 mm strap width

The MST6 tool has been specially developed for reliably applying HellermannTyton metal cable ties of the MST-S series. Due to the punch-lock mechanism the tie is mechanically crimped and leads to metal deformation of the tie ends. This punch-lock mechanism ensures a reliable bundling with perfect resistance to vibration. The tension force is freely adjustable by the operator.

Features and benefits

- Tough metal tool
- Ergonomic design
- Consistent tensioning and automatically cutting of metal ties
- Designed for use with MST-S Series ties (5.9 mm)
- For tensioning, fixing and cutting MST-S metal ties only



MST6.



www.HellermannTyton.com/MST6-cat22

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MST6	MST6	5.9	0.3	0.532 kg	110-61000
SP MST6 replacement blade	Replacement Blade	-	-	0.003 kg	110-61001
SP MST6 replacement punch	Replacement Punch	-	-	0.001 kg	110-61002

All dimensions in mm. Subject to technical changes.

Manual tensioning tool for metal ties MST-Series

MST9 for 8.9 mm strap width

The MST9 tool has been specially developed for reliably applying HellermannTyton metal cable ties of the MST-M series. Due to the punch-lock mechanism the tie is mechanically crimped and leads to metal deformation of the tie ends. This punch-lock mechanism ensures a reliable bundling with perfect resistance to vibration. The tension force is freely adjustable by the operator.

Features and benefits

- Tough metal tool
- Ergonomic design
- Consistent tensioning and automatic cutting of metal ties
- Designed for use with MST-M Series ties (8.9 mm)
- For tensioning, fixing and cutting MST-M metal ties only



MST9.

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MST9	MST9	8.9	0.4	0.532 kg	110-13000
SP MST9 replacement blade	Replacement Blade	-	-	0.004 kg	110-13001
SP MST9 replacement punch	Replacement Punch	-	-	0.001 kg	110-13002

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!

www.HT.click/9-559



Application Tooling for Cutting Plastic Ties



EVO cut.
See page 561

25

Application Tooling for Snappers



MSNP, ASNP.
See page 562



ASNP.
See page 562

Application Tooling for Heat Shrinkable Tubing



H6100.
See page 564

30



CHG900.
See page 563

32

Application Tooling for Non Shrinkable Tubing



NA.
See page 565

35-38



VA.
See page 566

39-41



K, S, SS.
See page 567

Application Tooling for Braided Sleeves



HSG0.
See page 568

45

Application Tooling for Identification



HCT1, HCT2.
See page 569

50-51



Manual cutting tool for plastic ties

EVO cut

The EVO cut is a cutting tool for plastic ties, which ensures the cut of the strap while preserving wires and harnesses from being damaged. This applies to flexible cables, bundles and lines as well as rigid bundled goods. Its use is recommended in many applications for which wires and harnesses have a high value added. Especially for sensitive cable harnesses the use of the EVO cut is recommended.

The cutting tool is made of a lightweight plastic housing and an ergonomic, non-slip handle for a comfortable and secure grip.

The tool includes three interchangeable nosepieces for plastic cable ties of varying widths and thicknesses.

Features and benefits

- Cutting tool for plastic ties
- Tie can be cut off at any part of the strap
- Ensures the cable isolation from being damaged
- Light-weighting plastic housing, ergonomic design
- Single-handed operation
- Includes three interchangeable nosepieces for respective cable tie width and thickness



EVO cut - Cutting tool for plastic ties.



Tie can be cut off at any part of the strap.



www.HellermannTyton.com/EVOcut-cat22



Single-handed operation.

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
EVOcut	EVO cut	7.8	1.8	0.14 kg	110-05005

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!
www.HT.click/9-561





Snapper Tools

MSNP1-70 for Snapper Size 1 to 70

ASNP2-22 for Snapper Size 2 to 22

ASNP24-70 for Snapper Size 24 to 70

Features and benefits

- For efficient fixing of the snapper hose clips
- MSNP tool: handy for installation on site
- ASNP tool: suitable for series production. Retaining screw limits the draw-in area prevents overstretching of the snapper



Snapper Application Tools MSNP1-70 and ASNP24-70.



Snapper hose clips for tubes and harnesses see page 205.



Pneumatic Tools for Snapper are available on request. Contact us!



Snapper Application Tool ASNP2-22.

TYPE	Application	Weight	Material	Colour	Article-No.
MSNP1-70	SNP-Series 1 up to 70	0.18 kg	Metal (MET), Plastic (PL)	Yellow (YE)	191-01700
ASNP2-22	SNP-Series 2 up to 22	0.2 kg	Metal (MET), Plastic (PL)	Blue (BU)	191-02220
ASNP24-70	SNP-Series 24 up to 70	0.25 kg	Metal (MET), Plastic (PL)	Red (RD)	191-24700

Subject to technical changes.





Cordless Heat Gun - Gas powered

CHG900

The HellermannTyton CHG900 Cordless Heat Gun is powered by P445 gas cartridges, providing autonomous working of 90 minutes in one go. The tool is designed to produce flameless heat which makes it the ideal hot-air gun to apply a huge variety of heat shrink tubing and heat shrink wire markers as well as molded shapes or heat shrink boots, transition shapes, end caps and cable repair sleeves especially in harsh outdoor conditions covering freezing temperatures as low as -8 °C.

Features and benefits

- Cordless heat gun powered by P445 gas cartridges
- Flameless heat - no direct flame outlet
- 90 min autonomy per cartridge
- Qualified for harsh outdoor conditions (-8 °C)
- Lightweight 440 g tool (555 g incl. cartridge)
- Hands-free operation due to integrated standing pod
- Quick start piezo ignition
- Instant turnaround due to antifiare feature
- Precise gas flow adjustment
- Ergonomic rugged design
- Quick gas cartridge exchange
- Tool-free maintenance



HellermannTyton Cordless Heat Gun Kit - CHG900.



Gas Nozzle for CHG900 Heat Gun.



Piezo Ignition Trigger for CHG900 Heat Gun.

TYPE	Description	Article-No.
CHG900	Cordless Heat Gun - CHG900 Set incl. P445 Gas Cartridge and 2 nozzles.	391-90010
Piezo CHG900	CHG900 Spare Part - Piezo Ignition Trigger.	391-90011
Gas Nozzle	CHG900 Spare Part - Gas Nozzle.	391-90012
P445	P445 Gas Cartridge (Butane, Propane, Propene).	391-90101

Subject to technical changes.



Add items to your watchlist!
www.HT.click/9-563





Electrical Hot Air Tool

H6100

H6100 Electrical Hot Air Tool is designed for shrinking thin to medium wall heat shrink tubing, end caps and molded shapes.

Features and benefits

- Ergonomic and light weight hand tool
- Fatigue-free working due to low weight less than 1 kg
- Powerful 1600 W motor
- Non-slip rubber ring for safe work bench application
- Infinitely variable temperature setting up to +700 °C
- Ceramic heating element
- Integrated easy to clean air filter
- Heavy duty H07RN-F power cord
- Sturdy tool case incl. 3 push-on nozzles for precise heat shrink applications



H6100 Electrical Hot Air Gun.



H6100 comes in carrying case incl. push-on nozzles.



Adjusting H6100 operation temperature.

TYPE	Air Flow l/min	Operating Temperature	Standby Temp. °C	Wattage	Operational Voltage	Weight	Article-No.
H6100	240 l/min	+40 °C to +700 °C	40 °C	1,600 W	230 V	0.99 kg	391-00110

Subject to technical changes.





Three-pronged pliers for sleeves and grommets

NA


Three-pronged expansion tools are used to ensure speedy and precise application of expandable markers and sleeves.

Features and benefits


- To easy affix expandable sleeves of every type onto cables/connectors
- Push pliers and pull over cable
- Close pliers, sleeve is placed easily
- Hellerrine lubricant recommended for easy operation




Fast, secure application with the NA three-pronged pliers.




Replacement prong NA0/1




Replacement prong NA1K/3



Replacement prong NA4/5



Replacement prong NA8/10



Three-prong pliers $D = \text{max. application diameter}$

TYPE	Description	Bundle Ø min.	Bundle Ø max.	Ø D max.	Max. length of marker	Article-No.
NA0/1	Expansion tool NA0/1	1.3	1.8	10.5	28	621-10001
NA1K/3	Expansion tool NA1/3	2.5	5.0	11.0	28	621-10103
NA4/5	Expansion tool NA4/5	7.5	10.0	15.5	50	621-10405
NA8/10	Expansion tool NA8/10	12.0	17.0	25.5	60	621-10810
NA0/1 PRONG	Replacement prongs for NA0/1	1.3	1.8	-	28	621-60001
NA1K/3 PRONG	Replacement prongs for NA1K/3	2.5	5.0	-	28	621-60103
NA4/5 PRONG	Replacement prongs for NA4/5	7.5	10.0	-	50	621-60405
NA8/10 PRONG	Replacement prongs for NA8/10	12.0	17.0	-	60	621-60810

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!
www.HT.click/9-565





Three-pronged pliers for sleeves and grommets

VA2.5/5 - reinforced

Expansion tools are used to ensure speedy and precise application of expandable markers and sleeves.

Features and benefits


- Suitable for expanding tubing cut lengths and rubber parts
- Withstands high loading
- Set of 3 2.5/5 pins
- Replacement pins available in sizes 8 and 18




For Hellerine lubricant see page 308.



VA2.5/5.




Replacement prong size 2.5/5



Replacement prong size 8



Replacement prong size 18



Three-prong pliers D = max. application diameter

TYPE	Description	Bundle Ø min.	Bundle Ø max.	Ø D max.	Article-No.
VA2.5/5	Expansion tool VA2.5/5	2.5	5.0	26.0	621-00200
VA-2.5/5 PRONG	Replacement prongs size 2.5/5	2.5	5.0	26.0	621-01200
VA2.5/5 PRONG 8	Replacement prongs size 8	8.0	10.0	28.0	621-02200
VA2.5/5 PRONG 18	Replacement prongs size 18	18.0	20.0	30.0	621-03200

All dimensions in mm. Subject to technical changes.





Three-pronged pliers for sleeves and grommets

K, S, SS

Three-pronged expansion tools are used to ensure speedy and precise application of expandable markers and sleeves.

Features and benefits


- For speedy application of markers and sleeves
- Hellerine lubricant recommended for easy operation
- Handy D KIT contains a tool body, a range of prongs and small bottle of Hellerine lubricant.



Fast, secure application with the three-pronged expansion tools.



For Hellerine lubricant see page 308.



Three-prong pliers D = max. application diameter

TYPE	Description	Bundle Ø min.	Bundle Ø max.	Ø D max.	Max. length of marker	Article-No.
SS TOOL	Three-pronged plier	1.2	2.0	15.0	20	621-80008
S TOOL	Three-pronged plier	2.5	4.0	15.0	20	621-80009
K TOOL	Three-pronged plier	5.0	10.0	17.0	32	621-80007
D KIT	Three-pronged plier kit	1.2	11.5	17.0	32	621-80005

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!

www.HT.click/9-567





Hot cutting tool

HSG0

The HSG0 hand tool is used to cut braided sleeving cleanly and without fraying.

Features and benefits

- Light and sturdy
- Heats up quickly with the press of button and cuts in seconds
- The yarn melts and fuses together
- No fraying of the sleeving



The HSG0 hot cutting tool prevents the braided sleeving from fraying.



www.HellermannTyton.com/HSG0-cat22

TYPE	Description	Weight	Colour	Article-No.
HSG0	Hot cutting tool	1.15 kg	Blue (BU)	170-99001
HSG0BLADE	Replacement blade	0.027 kg	Metal (ML)	170-99002

Subject to technical changes.





Helafix Tool

HCT1 for carrier size HCR09

HCT2 for carrier size HCR12

HCT1 and HCT2 tools are ideal for cleanly cutting the carrier strip as well as punching out the securing holes. For HCR06, HCR18 and HCR24, the front part of the pliers can be used. To fix the character holders HC and HCR simply use the T18 range of cable ties, fixings or rivets.

Features and benefits

- Cleanly cut Helafix HCR carrier tubing
- Punch securing holes on edges of HCR09 (HCT1) and HCR12 (HCT2)
- Apply punched HCR09 and HCR12 with T18 range of cable ties
- Suitable for punching rivet holes in HCR06, HCR18 and HCR24 tubing
- Punch hole diameter 2.5 mm
- Fix with T18 range of cable ties or suitable rivets



Any length can be used...



...just cut to suit.

TYPE	For Carrier Width	For Size	Ø (D)	Article-No.
HCT1	10.0	HCR09	2.5	525-00010
HCT2	13.0	HCR12	2.5	525-00013

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!
www.HT.click/9-569

